



TRELLEBORG

TRELLEBORG SK-900



SK-800 & SK-900 TOTAL SOLUTION

10-16.5 8P.R. NMS

SKID STEER TIRES

The Trelleborg Skid Steer product offering was developed to work well in a variety of abrasive applications on equipment ranging from skid steer loaders, aerial/boom lifts, backhoes and all-terrain forklifts. These tires have a wide lug tread pattern that provides optimal grip and traction on both smooth and rough surfaces. The high quality tread compound promotes maximum tire life and increased cut and chip resistance.

This addition to our traditional pneumatic product - and compliment to our solid skid steer product offering - further extends Trelleborg's tire line to offer more total solutions.

- Natural Rubber
- High Stability / Maximum Safety
- Extended Tire Life
- Optimal Grip and Traction

SK-900

- Reinforced sidewall rim guard for increased protection against side impacts
- Premium compounds for maximum tire life and good cut/chipping resistance
- A flat profile for increased surface contact and stability
- Trelleborg engineered
- Designed for heavy duty use
- Excellent ride quality

SK-800

- Designed for general purpose use in construction and industrial applications
- Aggressive tire design with rim guard
- Trelleborg engineered
- Cost effective tire

TRELLEBORG SK-900

SIZE	PLY RATING	RIM WIDTH	LOAD RATING @ 5 MPH LBS	INFLATION PRESSURE PSI	INFLATION PRESSURE BAR	INFLATED OUTSIDE DIAMETER IN.	INFLATED SECTION WIDTH IN.	WEIGHT LBS
10-16.5	8	8.25	4,140	60	4.1	30.0	10.0	55
12-16.5	10	9.75	5,600	65	4.5	32.0	13.0	73
14-17.5	14	10.5	8,540	80	5.5	35.0	14.0	112
15-19.5	14	11.75, 12.25	10,060	70	4.8	39.5	15	140

TRELLEBORG SK-800

SIZE	PLY RATING	RIM WIDTH	LOAD RATING @ 5 MPH LBS	INFLATION PRESSURE PSI	INFLATION PRESSURE BAR	INFLATED OUTSIDE DIAMETER IN.	INFLATED SECTION WIDTH IN.	WEIGHT LBS
23 x 8.5-12	6	7.00	1,810	50	3.4	22.7	8.6	24
27 x 8.5-15	8	8.50	2,890	60	4.0	27.2	8.6	31
10 x 16.5	8	8.25	4,140	60	4.1	30.0	10.0	48
10 x 16.5	10	8.25	4,710	75	5.2	30.0	10.0	49
12 x 16.5	10	9.75	5,600	65	5.0	32.0	12.0	66

